

**Amendments to the Claims**

Without prejudice, this courtesy listing of the claims replaces all prior versions and listings of the claims in the present application:

**Listing of the Claims:**

Claims 1-8 (Canceled).

9. (Currently Amended) A system, comprising:

a plurality of sensors, each sensor including a transmitter and a receiver for signals, wherein:

one of the sensors being able to receive a cross echo signal of another of the sensors,  
each of the sensors ~~one of~~ receives and analyzes ~~one of~~ self-echo signals and cross echo signals only for specific intervals relating to a time delay of a reception signal in relation to a transmission signal of its own, and

a phase angle of the repetition frequency  $f_w$  of the transmission signal is selected differently for each sensor.

10. (Currently Amended) The system as recited in Claim [[8]] 9, wherein the sensors include one of communicating radar sensors, communicating optical sensors, and communicating ultrasound sensors.

11. (Currently Amended) The radar system as recited in Claim [[9]] 10, wherein a carrier signal modulated by a PN code using one of ASK, PSK, BPSK, FSK, and a combination of at least two of ASK, PSK, BPSK, and FSK is used for the transmission signals of the radar sensors.

12. (Currently Amended) The radar system as recited in Claim [[10]] 11, wherein each of the radar sensors monitors a distance range ( $r_a; r_b$ ) to be monitored from the interval (0m;  $R_{max}$ ) where:  $0m \leq r_a \leq r_b \leq R_{max}$ .

13. (Canceled).

**U.S. Pat. Appl. Ser. No. 10/583,290**  
**Attorney Docket No. 10191/4753**  
**Reply to Office Action of September 17, 2008**

14. (Currently Amended) The radar system as recited in Claim [[9]] 10, wherein a first radar sensor receives the cross echoes of n-1 additional communicating radar sensors in the distance ranges  $(e/2t_{s2...n})+r_a; e/(2t_{s2...n})+r_b \} [c/(2t_{s2...n})+r_a; c/(2t_{s2...n})+r_b]$ .

15. (Currently Amended) The radar system as recited in Claim [[9]] 10, wherein each radar sensor has a plurality of receivers, and wherein a self-echo signal and (n-1) cross echo signals are evaluated at least one of simultaneously and sequentially in a radar sensor when simultaneous evaluation of [[a]] the plurality of receivers is provided.